


THE SELF USE  
SMART INVERTER

NEW GENERATION



**IMEON ENERGY**  
Your Power, Your Rules



GRID-TIE



OFF-GRID



INTELLIGENT  
STORAGE



30% MORE  
EFFICIENCY <sup>(1)</sup>



PLUG & PLAY  
INSTALLATION

# Self Use Smart Grid Inverter



New IMEON 3.6  
3kW PV input, 6kW AC output

Thanks to IMEON 3.6, the self-produced solar energy is intelligently oriented and used to an optimal performance.

Its innovative conception allows to reduce the number of energy storage cycles, all while significantly increasing its capacity and life.

## SMART GRID

With the smart management and the real time multi energy phase-coupling, IMEON 3.6 optimises the yield by choosing itself the ideal energy mode: direct consumption (self use), storing the surplus, using the grid, and / or injecting the energy surplus to the grid. It adapts automatically to the installation without any complex configurations.

## ECONOMIC

No more need for solar chargers, commutators or additional inverters. The clever energy management and all-in-one features of IMEON 3.6 help reduce the price of the photovoltaic electricity down to 30%<sup>(1)</sup>. Its innovative Smart Grid function also allows to lower the storage capacity and cycles, as well as further prolonging the battery life.

## ALL IN ONE

IMEON 3.6 is conceived for all solar installation types: isolated sites (Off-Grid), connected to the grid (Grid-Tie), hybrid (On and Off-Grid). It replaces inverters, load regulator, commutator, etc. IMEON 3.6 is a Plug & Play smart inverter, simplifying the implementation of a solar system and thereby also reducing an otherwise long installation time.

<sup>(1)</sup> According to condition of use

GRID AC (ON-GRID & OFF-GRID)	IMEON 3.6
Nominal output power	3000 W
Maximum output power	6000 W <sup>(2)</sup>
AC voltage (input & output)	230 Vac (±15 %) / 50 Hz (±5 %)
Nominal output current	13 A
Maximum output current	26 A <sup>(2)</sup>
Feed in to grid	Programmable (yes by default)
Energy consumption	Programmable priorities (PV / Storage / Grid)
<b>SOLAR INSTALLATION</b>	
Maximum input power	3 150 W
Start-up voltage	150 V
Number of MPPT inputs	1
MPPT voltage range	120V – 450V
Maximum input current	18 A
Maximum input voltage	510 V
Maximum efficiency	DC to AC : >95,5% (94,5% EU)
Solar production use	Programmable priorities (PV / Storage / Grid)
<b>BATTERY &amp; CHARGE</b>	
DC voltage	48 Vdc
Maximum discharge current	80 A
Maximum load current	25 A
Type of batteries	Gel, AGM
Charging curve	3-phase (Bulk / Absorption / Float)
Maximum efficiency	PV to battery : >94% / Battery to AC : >93%
Battery charge	Programmable (threshold / timing range via AC Grid)
Battery discharge	Programmable ( 2 thresholds according to grid availability)
<b>GENERAL</b>	
Dimensions (w x h x d in mm)	540 x 440 x 135
Protection category	IP 20
Weight	18 kg
Connectivities	TL (transformless)
Connectors	USB / Modbus / Ethernet - IP (option)
Conditions of use	Humidity level: 5 to 90% without condensation T°C: 0 à + 50°C, degressive power >40°C (15w/°C)
Standards	EN 62109-2 / EN 62109-1 / EN 62040-1 DIN V VDE V 0126-1-1 (+VFR2013) / VDE-AR-N 4105 / DIN VDE V 0124-100
Guarantee	5 years / Extensions to 10 years (optional)

<sup>(2)</sup> Maximum possible overload power with grid activated. Refer to installation manual.

